



PRODUCT SPECIFICATION

A66FHLW

Control System	Pulse width modulation control		
Refresh Rate	333Hz		
Neutral Position	1520µS		
Signal Mode	Digital		
Dead band	2 µSec		
Operating Voltage	4.8V ~ 8.4V		
Operating Temperature	-15C° ~ +70C°		
Bearing	2BB		
Mechanical Angle	No Limit		
Size	40.8*20.2*29.5mm		
Net Weight	75.8g		
Wire	TYU 300mm / 22AWG		
Operating Travel	180°±10°		
Signal Range	500 to 2500 µSec		
Stall Torque	41 kg-cm (569 oz-in) @ 4.8V 46 kg-cm (639 oz-in) @ 6.0V 53 kg-cm (736 oz-in) @ 7.4V 60 kg-cm (834 oz-in) @ 8.4V	Unload Current 460mA @ 4.8V 500mA @ 6.0V 540mA @ 7.4V 580mA @ 8.4V	UNIT:MM
Operating Speed	0.145sec/60° @ 4.8V 0.132sec/60° @ 6.0V 0.115sec/60° @ 7.4V 0.100sec/60° @ 8.4V	Loading Current 5400mA @ 4.8V 6000mA @ 6.0V 6800mA @ 7.4V 7500mA @ 8.4V	
Direction	<input checked="" type="checkbox"/> CCW <input type="checkbox"/> CW		
Waterproof Level	<input type="checkbox"/> IP65 <input checked="" type="checkbox"/> IP67		
Angle Sensor	<input type="checkbox"/> Potentiometer <input checked="" type="checkbox"/> Magnet Angle Sensor		
Motor Type	<input checked="" type="checkbox"/> 4-Pole Brushless <input type="checkbox"/> Coreless <input type="checkbox"/> DC		
Motor Drive	<input checked="" type="checkbox"/> FET Drive <input type="checkbox"/> IC Drive <input type="checkbox"/> Transistor Drive		
Programmable	<input checked="" type="checkbox"/> Yes <input type="checkbox"/> No		
Gear Material	<input checked="" type="checkbox"/> Strength Steel <input type="checkbox"/> Titanium <input type="checkbox"/> Copper <input type="checkbox"/> Plastic		
Horn Gear Spline	<input checked="" type="checkbox"/> 25T-φ5.92mm <input type="checkbox"/> 25T-φ4.94mm <input type="checkbox"/> Other_____		
Case Material	<input checked="" type="checkbox"/> AL6061T6 <input type="checkbox"/> Aluminum + Plastic <input type="checkbox"/> Plastic		
Bearing Material	<input checked="" type="checkbox"/> Metal <input type="checkbox"/> Plastic		
Horn Accessories	<input checked="" type="checkbox"/> AL6061T6 <input checked="" type="checkbox"/> Plastic		
Wire Color	Negative: <input checked="" type="checkbox"/> Black <input type="checkbox"/> Brown Positive: <input checked="" type="checkbox"/> Black <input type="checkbox"/> Red Signal: <input checked="" type="checkbox"/> Grey <input type="checkbox"/> White <input type="checkbox"/> Orange		