



PRODUCT SPECIFICATION

A80BHSW V2

Control System	Pulse width modulation control		
Refresh Rate	333Hz / 666Hz		
Neutral Position	1520µS / 760µS		
Signal Mode	Digital		
Dead band	2 µSec		
Operating Voltage	4.8V ~ 8.4V		
Operating Temperature	-15C° ~ +70C°		
Bearing	3BB		
Mechanical Angle	No Limit		
Size	40*20*37.5mm		
Net Weight	79g		
Wire	TYU 300mm / 22AWG		
Operating Travel	180°±10°		
Signal Range	500 to 2500 µSec		
Stall Torque	23 kg-cm (319 oz-in) @ 4.8V 28 kg-cm (389 oz-in) @ 6.0V 33 kg-cm (458 oz-in) @ 7.4V 36 kg-cm (500 oz-in) @ 8.4V	Unload Current 280mA @ 4.8V 310mA @ 6.0V 360mA @ 7.4V 400mA @ 8.4V	
Operating Speed	0.120sec/60° @ 4.8V 0.110sec/60° @ 6.0V 0.083sec/60° @ 7.4V 0.071sec/60° @ 8.4V	Loading Current 3600mA @ 4.8V 4000mA @ 6.0V 4300mA @ 7.4V 4600mA @ 8.4V	
Direction	<input checked="" type="checkbox"/> CCW <input type="checkbox"/> CW		
Waterproof Level	<input type="checkbox"/> IP65 <input checked="" type="checkbox"/> IP67		
Angle Sensor	<input type="checkbox"/> Potentiometer <input checked="" type="checkbox"/> Magnet Angle Sensor		
Motor Type	<input checked="" type="checkbox"/> Brushless <input type="checkbox"/> Coreless <input type="checkbox"/> DC		
Motor Drive	<input checked="" type="checkbox"/> FET Drive <input type="checkbox"/> IC Drive <input type="checkbox"/> Transistor Drive		
Programmable	<input checked="" type="checkbox"/> Yes <input type="checkbox"/> No		
Gear Material	<input checked="" type="checkbox"/> Strength Steel <input checked="" type="checkbox"/> Titanium <input type="checkbox"/> Copper <input type="checkbox"/> Plastic		
Horn Gear Spline	<input checked="" type="checkbox"/> 25T-φ5.92mm <input type="checkbox"/> 25T-φ4.94mm <input type="checkbox"/> Other _____		
Case Material	<input checked="" type="checkbox"/> AL6061T6 <input type="checkbox"/> Aluminum + Plastic <input type="checkbox"/> Plastic		
Bearing Material	<input checked="" type="checkbox"/> Metal <input type="checkbox"/> Plastic		
Horn Accessories	<input type="checkbox"/> AL6061T6 <input checked="" type="checkbox"/> Plastic		
Wire Color	Negative: <input checked="" type="checkbox"/> Black <input type="checkbox"/> Brown Positive: <input checked="" type="checkbox"/> Black <input type="checkbox"/> Red Control Signal: <input checked="" type="checkbox"/> Grey <input type="checkbox"/> White <input type="checkbox"/> Orange		