



PRODUCT SPECIFICATION

SA30BHM

Control System	Pulse width modulation control		<p style="text-align: center;">UNIT:MM</p>
Refresh Rate	333Hz		
Neutral Position	1520µS		
Signal Mode	Digital		
Dead band	2 µSec		
Operating Voltage	4.8V ~ 8.4V		
Operating Temperature	-15C° ~ +70C°		
Bearing	2BB		
Mechanical Angle	No Limit		
Size	29*14*29mm		
Net Weight	32g		
Wire	TYU 180mm / 26AWG		
Operating Travel	180°±10°		
Signal Range	500 to 2500 µSec		
Stall Torque	8.0 kg-cm (111 oz-in) @ 4.8V 9.0 kg-cm (125 oz-in) @ 6.0V 10.50 kg-cm (145 oz-in) @ 7.4V 11.50 kg-cm (159 oz-in) @ 8.4V	Unload Current	150mA @ 4.8V 180mA @ 6.0V 240mA @ 7.4V 300mA @ 8.4V
Operating Speed	0.100sec/60° @ 4.8V 0.082sec/60° @ 6.0V 0.068sec/60° @ 7.4V 0.060sec/60° @ 8.4V	Loading Current	2000mA @ 4.8V 2300mA @ 6.0V 2800mA @ 7.4V 3000mA @ 8.4V
Direction	<input checked="" type="checkbox"/> CCW <input type="checkbox"/> CW		
Waterproof Level	<input type="checkbox"/> IP65 <input type="checkbox"/> IP67		
Angle Sensor	<input checked="" type="checkbox"/> Potentiometer <input type="checkbox"/> Magnet Angle Sensor		
Motor Type	<input checked="" type="checkbox"/> Brushless <input type="checkbox"/> Coreless <input type="checkbox"/> DC		
Motor Drive	<input checked="" type="checkbox"/> FET Drive <input type="checkbox"/> IC Drive <input type="checkbox"/> Transistor Drive		
Programmable	<input checked="" type="checkbox"/> Yes <input type="checkbox"/> No		
Gear Material	<input checked="" type="checkbox"/> Strength Steel <input type="checkbox"/> Titanium <input type="checkbox"/> Copper <input type="checkbox"/> Plastic		
Horn Gear Spline	<input checked="" type="checkbox"/> 25T-φ5.92mm <input type="checkbox"/> 5T-φ4.94mm <input type="checkbox"/> Other_____		
Case Material	<input checked="" type="checkbox"/> AL6061T6 <input type="checkbox"/> Aluminum + Plastic <input type="checkbox"/> Plastic		
Bearing Material	<input checked="" type="checkbox"/> Metal <input type="checkbox"/> Plastic		
Horn Accessories	<input type="checkbox"/> AL6061T6 <input checked="" type="checkbox"/> Plastic		
Wire Color	Negative: <input checked="" type="checkbox"/> Black <input type="checkbox"/> Brown Positive: <input type="checkbox"/> Black <input checked="" type="checkbox"/> Red Signal: <input type="checkbox"/> Grey <input checked="" type="checkbox"/> White <input type="checkbox"/> Orange		